

5 OUTBOARD
YEARS
warranty

FOR LEISURE USE ONLY
Subject to terms and conditions
see your Dealer for more
information.

QuattroT
XSR

QuattroT



f Selva Marine Hrvatska
i Selva Marine Hrvatska



OUTBOARD
MOTORS



10 MODELS FROM
25HP TO 2X300HP IN 22 VERSIONS

Burning acceleration and low consumption are the main characteristics of the Selva Marine 4-stroke range for leisure, professional or commercial use. So they are specially developed for the most demanding people. The advanced electronic system controls all the engine's functions in the best way and gives breathtaking performance and fuel economy.



34 MODELS FROM
2,5HP TO 2X300HP IN 105 VERSIONS

This Selva Marine range has a strong and distinctive personality that operates in total respect of nature. The use of sophisticated technologies, their compactness, elegant and innovative design make these outboard motors a range that does not go unnoticed in the pleasure boating sector.

Amberjack

25XSR



Dorado E.F.I.

60XSR



Murena E.F.I.

70XSR



Spearfish E.F.I.

100XSR



TECHNICAL CHARACTERISTICS

NEW

Model	AMBERJACK	DORADO	MURENA	SPEARFISH
Power (hp)	25 XSR EFI	60 XSR EFI	70 XSR EFI	100 XSR EFI
Power (kW)	18.4	44.1	51.5	73.6
Max. R.P.M.	5000 / 6000		5300/6300	5000/6000
Motor type	4 temps SOHC			
Swept volume c.c.	432	996		1832
Bore x Stroke (mm)	65 x 65.1	65x75		81x88.9
N° Cylinders	2 in-line		4 in-line	
Induction	Electronic Injection			
Choke	Automatic			
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Separate 23			Not provided
Lubrication	Forced (oil sump)			
Ignition	C.D.I. Micro-computer		T.C.I. / Computer	
Ignition timing	Electronic			
Starting	Manual or Electric		Electric	
Alternator	Standard 12V/190 W (regulator optional) on Manual start version Standard 12V/190 W with regulator on Electric start version		Standard 12V/200W with regulator	Standard 12V/420W with regulator
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box according to version		Remote with remote control box	
Type of remote control box provided (for the version with remote control box)	Single remote control box with safety switch			
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version		Power Trim/Tilt	
Gears	Mechanical F-N-R			
Transmission Ratio	13 / 27		12/28	13/28
Available shaft versions	C. - L.	L.	L.-XL.	
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	56		111	119

Some models may not be available in all countries or they may have different, non-standard horsepower depending on the different national legislative requirements. (For further details see the current price list.)
The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights etc. without any forewarning or obligations.

Swordfish E.F.I.

115XSR



Killer Whale E.F.I.

150XSR



Sei Whale E.F.I.

200XSR



White Whale E.F.I.

300XSR



TECHNICAL CHARACTERISTICS

Model	SWORDFISH	KILLER WHALE	SEI WHALE	WHITE WHALE ^{NEW}
Power (hp)	115 XSR EFI	150 XSR EFI	200 XSR EFI	300 XSR EFI
Power (kW)	84,6	110,3	147,1	220,7
Max. R.P.M.	5300/6300		5000/6000	
Motor type	4 Stroke DOHC - 16V		4 Stroke DOHC - 16V at variable timing	4 stroke DOHC - 24V with VTC direct acting
Swept volume c.c.	1832	2670	2785	4169
Bore x Stroke (mm)	81x88,9	94x96,2	96 x 96,2	96 x 96
N° Cylinders	4 on line			6 a V 60°
Induction	Electronic Injection			
Choke	Automatic			
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Not provided			
Lubrication	Forced (oil sump)			
Ignition	T.C.I./Computer			
Ignition timing	Electronic			
Starting	Electric			
Alternator	Standard 12V /420W with rectifier		Standard 12V / 500W with rectifier	Standard 12V / 840W with rectifier
Cooling	A eau avec circulation forcée par pompe			
Exhaust	Sous-marin à travers le moyeu de l'hélice			
Steering system	Remote with remote control box		Remote control box with electronic control Drive By Wire	
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch	Remote control box with electronic control Drive By Wire	Remote control box with electronic control Drive By Wire	
Trim adjustment	Power Trim/Tilt			
Gears	Mechanical F-N-R		Mechanical F-N-R electronic, operating Drive by Wire	
Transmission Ratio	13/28	14/28	14/26	21/12
Available shaft versions	L-XL		XL	XL - UL
Standard propeller type	3-bladed with built-in spring drive			
Weight basic version (kg)	175	216	227	260

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

COUNTER ROTATING PAIR

Sei Whale E.F.I.

2x200XSR



White Whale E.F.I.

2x300XSR



TECHNICAL CHARACTERISTICS

Model	COUNTER ROTATING PAIR	
	SEI WHALE	WHITE WHALE
Power (hp)	2 x 200 XSR EFI	
Power (kW)	2 x 300 XSR EFI	
Max. R.P.M.	2 x 147,1	
Motor type	5000 / 6000	
Swept volume c.c.	4 Stroke DOHC - 16V at variable timing	4 stroke DOHC - 24V with VTC direct acting
Bore x Stroke (mm)	2 x 2785	2 x 4169
N° Cylinders	2 x 96 x 96,2	2 x 96 x 96
Induction	2 x 4 on line	
Choke	Electronic Injection	
Fuel	Automatic	
Fuel tank (L)	Petrol (for specifications see the user manual)	
Lubrication	Not provided	
Ignition	Forced (oil sump)	
Ignition timing	T.C.I./Computer	
Starting	Electronic	
Alternator	Standard 2 x 12V / 500W with rectifier	Standard 2 x 12V / 840W with rectifier
Cooling	Water cooled with pump-forced circulation	
Exhaust	Underwater through propeller	
Steering system	Remote control box with electronic control Drive By Wire	
Type of remote control box provided (for the version with remote control box)	Twin lever with electronic binnacle Drive by Wire with safety switch	
Trim adjustment	Power Trim/Tilt	
Gears	Mechanical F-N-R electronic, operating Drive by Wire	
Transmission Ratio	14/26	21/12
Available shaft versions	XL	XL - UL
Standard propeller type	3-bladed with built-in spring drive	
Weight basic version (kg)	2 x 227	2 x 260

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

Pike

9.9



Wahoo

15



Wahoo

20



TECHNICAL CHARACTERISTICS

Amberjack E.F.I.

25



Model	PIKE		WAHOO		AMBERJACK
Power (hp)	9,9		15	20	25 EFI
Power (kW)	7,3		11	14,7	18,4
Max. R.P.M.	5000 / 6000				
Motor type	4 temps SOHC				
Swept volume c.c.	212		362		432
Bore x Stroke (mm)	56 x 43		63 x 58,1		65 x 65,1
N° Cylinders	2 in-line				
Induction	1 carburettor			Electronic Injection	
Choke	Manual		Automatic		
Fuel	Petrol (for specifications see the user manual)				
Fuel tank (L)	Separate 12			Separate 23	
Lubrication	Forced (oil sump)				
Ignition	C.D.I. Micro-computer				
Ignition timing	Electronic				
Starting	Manual or Electric				
Alternator	Standard 12V/70W (regulator optional) on Manual start version Standard 12V/70W with regulator on Electric start version		Standard 12V/120W (regulator optional) on Manual start version Standard 12V/120W with regulator on Electric start version		Standard 12V/190W (regulator optional) on Manual start version Standard 12V/190W with regulator on Electric start version
Cooling	Water cooled with pump-forced circulation				
Exhaust	Underwater through propeller				
Steering system	Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box according to version				
Type of remote control box provided (for the version with remote control box)	Single lever with safety switch				
Trim adjustment	Manual (4 pos) with trim for navigation in shallow waters		Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version		Manual (4 pos) with trim for navigation in shallow waters or Power Tilt depending on the version
Gears	Mechanical F-N-R				
Transmission Ratio	13 / 27				
Available shaft versions	C. - L.				
Standard propeller type	3-bladed with built-in spring drive				
Weight basic version (kg)	39,9		51,7		56

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details consult the current price list).

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

Aruana E.F.I.

40



Dorado E.F.I.

50



Dorado E.F.I.

60



TECHNICAL CHARACTERISTICS

Murena E.F.I.

70



Model	ARJANA		DORADO		MURENA
	40 EFI	50 EFI	60 EFI	70 EFI	
Power (hp)		36,8	44,1	51,5	
Power (kW)	29,4				
Max. R.P.M.		5000 - 6000		5300 - 6300	
Motor type		4 Stroke SOHC		4 Stroke SOHC - 16V	
Swept volume c.c.	747		996		
Bore x Stroke (mm)		65 x 75			
N° Cylinders	3 in-line		4 in-line		
Induction		Electronic injection			
Choke		Automatic			
Fuel		Petrol (for specifications see the user manual)			
Fuel tank (L)		Separate 23			
Lubrication		Forced (oil sump)			
Ignition		T.C.I./Computer			
Ignition timing		Electronic			
Starting		Electric			
Alternator	Standard 12V/190W with regulator		Standard 12V/200W with regulator		
Cooling		Water cooled with pump-forced circulation			
Exhaust		Underwater through propeller			
Steering system		Tiller bar steering with twist grip throttle control and steering friction adjustment or remote with remote control box, depending on the version		Remote with remote control box	
Type of remote control box provided (for the version with remote control box)		Single remote control box with safety switch			
Trim adjustment		Servo-assisted with Hydraulic shock absorber or Power Trim/Tilt depending on the version		Power Trim/Tilt	
Gears		Mechanical F-N-R			
Transmission Ratio	13 / 26		13 / 24		12 / 28
Available shaft versions			L		L-XL
Standard propeller type		3-bladed with built-in spring drive			
Weight basic version (kg)	99		111		119

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

Spearfish E.F.I.

80xs/100



Swordfish E.F.I.

115



Killer Whale E.F.I.

150



Sei Whale E.F.I.

200



TECHNICAL CHARACTERISTICS

Model	SPEARFISH		SWORDFISH	KILLER WHALE	SEI WHALE
	80 XS EFI	100 EFI	115 EFI	150 EFI	200 EFI
Power (hp)	58,8	73,6	84,6	110,3	147,1
Power (kW)	58,8	73,6	84,6	110,3	147,1
Max. R.P.M.	5000 / 6000		5300 / 6300	5000 / 6000	
Motor type	4 Stroke SOHC - 16V		4 Stroke DOHC - 16V		4 Stroke DOHC - 16V at variable timing
Swept volume c.c.	1832		2670		2785
Bore x Stroke (mm)	81 x 88,9		94x96,2		96 x 96,2
N° Cylinders	4 in-line				
Induction	Electronic Injection				
Choke	Automatic				
Fuel	Petrol (for specifications see the user manual)				
Fuel tank (L)	Not provided				
Lubrication	Forced (oil sump)				
Ignition	T.C.I./Computer				
Ignition timing	Electronic				
Starting	Electric				
Alternator	Standard 12V/420W with regulator				Standard 12V/500W with regulator
Cooling	Water cooled with pump-forced circulation				
Exhaust	Underwater through propeller				
Steering system	Remote with remote control box				Remote control box with electronic control Drive By Wire
Type of remote control box provided (for the version with remote control box)	Single remote control box with safety switch			Single binnacle lever with safety switch	Single lever with electronic binnacle Drive by Wire with safety switch
Trim adjustment	Power Trim/Tilt				
Gears	Mechanical F-N-R				Mechanical F-N-R electronic, operating Drive by Wire
Transmission Ratio	13/28		14/28		14/26
Available shaft versions	L - XL				XL
Standard propeller type	3-bladed with built-in spring drive				
Weight basic version (kg)	162		175	216	227

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

Beaked Whale E.F.I.

225



Right Whale E.F.I.

250



White Whale E.F.I.

300



TECHNICAL CHARACTERISTICS

Model	BEAKED WHALE	RIGHT WHALE	WHITE WHALE
Power (hp)	225 EFI	250 EFI	300 EFI
Power (kW)	165,5	183,9	220,7
Max. R.P.M.	5000/6000		
Motor type	4 stroke DOHC - 24V with VTC direct acting		
Swept volume c.c.	4169		
Bore x Stroke (mm)	96 x 96		
N° Cylinders	6 a V 60°		
Induction	Electronic Injection		
Choke	Automatic		
Fuel	Petrol (for specifications see the user manual)		
Fuel tank (L)	Not provided		
Lubrication	Forced (oil sump)		
Ignition	T.C.I. / Computer		
Ignition timing	Electronic		
Starting	Electric		
Alternator	Standard 12V / 840W with regulator		
Cooling	Water cooled with pump-forced circulation		
Exhaust	Underwater through propeller		
Steering system	Remote control box with electronic control Drive By Wire		
Type of remote control box provided (for the version with remote control box)	Single lever with electronic binnacle Drive by Wire with safety switch		
Trim adjustment	Power Trim/Tilt		
Gears	Mechanical F-N-R , electronic, operating Drive by Wire		
Transmission Ratio	21/12		
Available shaft versions	XL	XL - UL	
Standard propeller type	3-bladed with built-in spring drive		
Weight basic version (kg)	260		

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and **Selva Marine** reserves the right to modify the technical characteristics, materials, the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

COUNTER ROTATING PAIR

Sei Whale E.F.I.

2x200



COUNTER ROTATING PAIR

Beaked Whale E.F.I.
Right Whale E.F.I.

2x225/250



COUNTER ROTATING PAIR

TECHNICAL CHARACTERISTICS

White Whale E.F.I.

2x300



COUNTER ROTATING PAIR

Modello	COUNTER ROTATING PAIR SEI WHALE	COUNTER ROTATING PAIR BEAKED WHALE	COUNTER ROTATING PAIR RIGHT WHALE	COUNTER ROTATING PAIR WHITE WHALE
Power (hp)	2 x 200 EFI	2 x 225 EFI	2 x 250 EFI	2 x 300 EFI
Power (kW)	2 x 147,1	2 x 165,5	2 x 183,9	2 x 220,7
Max. R.P.M.	5000 / 6000			
Motor type	4-stroke DOHC - 16V at variable timing		4 stroke DOHC - 24V with VTC direct acting	
Swept volume c.c.	2 x 2785		2 x 4169	
Bore x Stroke (mm)	2 x 96 x 96,2		2 x 96 x 96	
N° Cylinders	2 x 4 in linea		2 x 6 a V 60°	
Induction	Electronic Injection			
Choke	Automatic			
Fuel	Petrol (for specifications see the user manual)			
Fuel tank (L)	Not provided			
Lubrication	Forced (oil sump)			
Ignition	T.C.I. / Computer			
Ignition timing	Electronic			
Starting	Electric			
Alternator	Standard 12V/500W with regulator	Standard 2 x 12V/840W with regulator		
Cooling	Water cooled with pump-forced circulation			
Exhaust	Underwater through propeller			
Steering system	Remote control box with electronic control Drive By Wire			
Type of remote control box provided (for the version with remote control box)	Twin lever with electronic binnacle Drive by Wire with safety switch			
Trim adjustment	Power Trim/Tilt			
Gears	Mechanical F-N-R electronic, operating Drive by Wire			
Transmission Ratio	14/26	21/12		
Available shaft versions	XL			XL - UL
Standard propeller type	3-bladed with built-in spring drive, counter rotating pair			
Weight basic version (kg)	2 x 227	2 x 260		

Some models may not be available in all countries, or they may have different, non-standard horse powers. Depending on the different national legislative requirements. (For further details see the current price list).

The data contained in this table are to be considered as approximate and Selva Marine reserves the right to modify the technical characteristics, materials, the right to modify the technical characteristics, materials, construction, weights, etc. without any forewarning or obligations.

ACCESSORIES

AVAILABLE ENGONES CONTROL

Mechanical controls



Drive by wire controls



Digital screen



Available propellers



GS aluminium series
for Aruana and Dorado



KS aluminium series
for Murena, Spearfish and Swordfish



KS Series Inox polished
for Spearfish and Swordfish



MS Series Inox polished
for Killer Whale and Sei Whale



TS Series Inox polished
for Beaked Whale, Right Whale and
White Whale



MXS Series In polished stainless steel
CNC precision machined
for Killer Whale and Sei Whale



TXS Series In polished stainless steel
CNC precision machined
for Beaked Whale, Right Whale and
White Whale



MS4 Series Polished stainless steel 4-blade
for Killer Whale, Sei Whale, Beaked
Whale, Right Whale and White Whale



SELVA MARINE HRVATSKA
PLATTNER CROATIA D.O.O.
ZAGREBAČKA CESTA 143A,
10000 ZAGREB, HRVATSKA
GSM: +385 (0) 91 6169 368
TEL: +385 (0) 23 49 333

www.selvamarine.hr

